

# DIODE(THREE PHASES BRIDGE TYPE)

# DF100LA/LB80/160




Power Diode Module DF100LA/LB is designed for three phase full wave rectification, which has six diodes connected in a three phase bridge configuration. The mounting base of the module is electrically isolated from semiconductor elements for simple heatsink construction output DC current is 100Amp ( $T_c=90^\circ\text{C}$ ) Repetitive peak reverse voltage is up to 1600V.

- $T_{j\text{MAX}}=150^\circ\text{C}$
- Isolated Mounting Base

**(Applications)**

AC. DC Motor Drive/AVR/Switching  
—for three phase rectification



**Maximum Ratings**

(Unless otherwise  $T_j=25^\circ\text{C}$ )


Symbol	Item	Ratings		unit
		DF100LA/LB80	DF100LA/LB160	
$V_{RRM}$	Repetitive Peak Reverse Voltage	800	1600	V
$V_{RSM}$	Non-Repetitive Peak Reverse Voltage	960	1700	V

Symbol	Item	Conditions	Ratings	unit	
$I_D$	Output Current (D.C.)	Three phase full wave, $T_c=90^\circ\text{C}$	100	A	
$I_{FSM}$	Surge Forward Current	$1/2$ cycle, 50/60Hz, Peak value, non-repetitive	1186/1300	A	
$T_j$	Operating Junction Temperature		$-40 \sim +150$	$^\circ\text{C}$	
$T_{stg}$	Storage Temperature		$-40 \sim +125$	$^\circ\text{C}$	
$V_{ISO}$	Isolation Breakdown Voltage (R.M.S.)	A.C. 1minute	2500	V	
	Mounting torque	Mounting (M5)	Recommended Value 1.5~2.5 (15~25)	2.7 (28)	N·m (kgf·cm)
		Terminal (M5)	Recommended Value 1.5~2.5 (15~25)	2.7 (28)	
	Mass	Typical Value	100	g	


**Electrical Characteristics**

Symbol	Item	Conditions	Ratings	unit
$I_{RRM}$	Repetitive Peak Reverse Current, max.	$T_j=150^\circ\text{C}$ , $V_R=V_{RRM}$	12	mA
$V_{FM}$	Forward Voltage Drop, max.	$I_F=100\text{A}$ , Inst. measurement	1.30	V
$R_{th(j-c)}$	Thermal Impedance, max.	Junction to case	0.23	$^\circ\text{C/W}$


### Maximum Forward Characteristics




### Output Current vs. Power Dissipation



### Output Current vs. Allowable case Temp



### Cycle Surge Forward Current Rating (Non-Repetitive)



### Transient Thermal Impedance

